

UNO S V

High Strength Cleaner/Degreaser

⇒ **Viscous formulation for inclined surfaces**

UNO S V is an aqueous based high strength degreaser which uses advanced cleaning technology to deliver outstanding performance. The excellent dissolving property of UNO S V allows the product to achieve optimal results at ambient temperature. The gel like consistency of UNO S V makes this product ideal for degreasing applications on inclined and vertical surfaces.

Features & Benefits:

- High strength concentrate, economical to use
- Can be diluted up to 1:40 to suit all cleaning needs
(note: dilution will reduce viscosity of the product)
- Achieves optimal results at ambient temperature
- For manual use (trigger sprayer)
- Removes oils, greases, organic contaminants, pigment coating, markers, smoke, dust, carbon deposits, etc.
- Built in corrosion inhibitors to prevent flash rusting
- Water-based, non-flammable
- Biodegradable, VOC free
- Solvent, phosphate and butyl-free
- Also available in foamy formulation (**UNO S**), foamless (**UNO S F**) and foamless with built in corrosion protection for parts which are sensitive to oxidation (**UNO S PF**).



Description	Size		Order No.	MSDS
	Metric	Imperial		
Sprayer	500ml	16.9 oz.	53-G 053	L-138F
Liquid	5L	1.3 gal.	53-G 056	L-138F
Liquid	20L	5.2 gal.	53-G 057	L-138F
Liquid	208L	55 gal.	53-G 058	L-138F

ACCESSORIES

Spout for 5L pail	53-L 113
Spout for 20L pail	53-L 207
Faucet for 208L drum, 2"	53-L 209
Faucet for 208L drum, ¾"	53-L 210
Replacement trigger sprayer	53-L 336

Technical information

Density	1.04 g/ml
Flashpoint	N/A
Odor/color	Apple scent, light tint
pH (at 100g/L H₂O)	<12
Viscosity	>800 centistokes
Rinsability	Excellent
VOC	0

MSDS available upon request or visit our web site at www.biocircle.com

UNO S V

High Strength Cleaner/Degreaser

⇒ Viscous formulation for inclined surfaces

Application dilution chart:

Equipment	Dilution ratio	Dilution %	Application	Material
Trigger sprayers	1:40 - 1:30	2,5% - 3,3%	Removal of light organic contaminants	Aluminum and Non-Ferrous Alloys, Plastics
Trigger sprayers	1:40 - 1:10	2,5% - 10%	Removal of light organic contaminants	Steel, Stainless Steel, plastic
Trigger sprayers	1:10 - Pure	10% - Pure	Removal of heavy organic contaminants	Steel, Stainless Steel

Dilution chart			
Dilution ratio	Dilution %	ml of cleaner/ 1L of water	Fl. oz. Of cleaner/ 1 gal of water
1:40	2,5%	25ml	3,2 fl. oz.
1:30	3,3%	33ml	4,3 fl. oz.
1:20	5%	50ml	6,4 fl. oz.
1:10	10%	100ml	12,8 fl. oz.
1:5	20%	200ml	25,6 fl. oz.
1:2	50%	500ml	64 fl. oz.