

SURFOX 204 Weld Cleaning System

The SURFOX electrochemical weld cleaning system is a highly effective method of removing heat tint in the heat affected zone of welded stainless steel (TIG, Spot and Pulsed MIG), without altering the surface of the parent material. It also promotes the formation of a uniform and durable chromium oxide passive layer to protect stainless steel against further corrosion. Surfox is a safer, faster and more cost effective alternative to very hazardous pickling pastes and abrasive weld cleaning processes like wire brushing and grinding.

The most versatile unit for a wide variety of jobs

SURFOX 204 is an industrial, self-contained weld cleaning system with an integrated electrolyte solution tank, a low level indicator and an automatic dispensing pump. A variable speed pump (manual or automatic) delivers the desired amount of electrolyte continuously to the work piece.

Features & benefits:

- Electrochemical cleaning with AC mode: settings low, medium, high (6-15 A)
- Marking option
- Electrochemical polishing in DC mode
- Vapour elimination system
- This system is equipped with a self-regulating inverter board, automatically
 monitoring and adjusting the current so as to ensure maximum cleaning
 effectiveness without loss of productivity.

The unit comes with:

- Variable current output knob, allowing the end user to pre-set the desired current level
- Wand with on/off pump cycling controls
- Electrical outlet for optional marking/etching hand piece
- Switchable output: AC mode for cleaning and marking, DC mode for polishing and etching
- Built in vapour elimination system useful when working in confined areas
- Compatible with all SURFOX electrolyte cleaning solutions
- Uses nitric and hydrofluoric acid free SURFOX electrolyte solutions
- The cleaning liquid is delivered automatically to the cleaning tip by an integrated pump system without spills, just the right amount and without stopping the cleaning action
- Cleaning of a typical TIG weld is done at a speed of 5 feet per minute
- No scrubbing or mechanical action required
- Instant cleaning of heat tint on welds
- ASTM A967 certified for chemical passivation for stainless steel

Description	Electrical		Dimensions			Tank	Lenght	Weight	Order No.
	Input	Output	Length	Width	Height	Capacity	of hose		
SURFOX machine	120V, 50/60 Hz,	12-30V AC	11'	4 ½"	6 ½"	64.2	13"	38.1 lbs	54-D 214
Model 204*	4.0A	15A				ounces		(17.3 Kg)	
SURFOX machine	120V, 50/60 Hz,	12-30V AC	11'	4 ½"	6 ½"	64.2	13"	38.1 lbs	54-D 264
Model 204*	4.0A	15A				ounces		(17.3 Kg)	
with Mini-Wand and									
brushes kit									

^{*}Standard equipment includes: 3 High Conductivity cleaning pads standard, 1 Teflon ring, 1 Standard tungsten insert, Drip guard, Ground wire with clamp, Carrying case





SURFOX 204 Weld Cleaning System

ACCESSORIES

Marking kits
Standard kit

SURFOX station

Station

PRO kit with stencil printer

Electrolyte solutions

Electrony te dolations	
SURFOX-T Heavy-Duty solution, 100ml	54-A 001
SURFOX-T Heavy-Duty solution, 1.5L	54-A 005
SURFOX-T Heavy-Duty solution, 20L	54-A 007
SURFOX-T Heavy-Duty solution, 208L	54-A 008
SURFOX-G Neutral pH solution, 100ml	54-A 061
SURFOX-G Neutral pH solution, 1.5L	54-A 065
SURFOX-G Neutral pH solution, 20L	54-A 067
SURFOX-G Neutral pH solution, 208L	54-A 068
SURFOX-N Cleaning & Neutralizing solution, 500ml	54-A 023
SURFOX-N Cleaning & Neutralizing solution, 20L	54-A 027
Cleaning pads and brushes	
Standard High Conductivity pads	54-B 026 (pack of 10)
Inside Corners High Conductivity pads	54-B 027 (pack of 10)
Narrow High Conductivity pads	54-B 028 (pack of 10)
Large High Conductivity pads for graphite insert	54-B 043 (pack of 10)
Mini-Wand and brushes kit	54-B 133
Carbon fiber flow-through brushes	54-B 029 (pack of 5)
Tungsten and graphite inserts	
Standard 90°	48-R 133
Standard 60°	54-B 016
Narrow 90°	54-B 017
Narrow 60°	54-B 018
Inserts kit (includes all 4 tungsten inserts)	54-B 012
Large graphite	54-B 009
Testers	
Stainless Steel Grade ID tester	54-T 001
Passivation tester	54-T 010

54-B 080

54-B 081

54-B 050