



Cleaning Abrasives

For your toughest cleaning & blending jobs!

FX cleaning abrasives are made from an industrial strength, non-woven webbing that is impregnated with precisely graded silicone carbide abrasive grains for fast material removal and a consistent surface finish. Their open structure ensures a cool operation without loading even when used on soft metals.

They will not gouge the metal surface, conform to both convex and concave surfaces and are excellent for cleaning welds, removing heavy paint, rust, scale, burn marks, gaskets, etc. They can replace wire brushes in many applications.

FX™ Cleaning Wheels

- Use on edge narrow contact area for maximum pressure
- Ideal for MIG and TIG weld cleaning and conditioning
- Can be used single or double loaded onto spindle









Dia.	Width	Arbor	Order No.	Optimal RPM	Max. RPM
4"	1/2"	1/2"	07-X 640	3500 to 4000	6000
6"	1/2"	1/2"	07-X 660	2400 to 2700	4000

FX™ Mounted Wheels

- Excellent for working in confined spaces
- For use on all power tools with chucks or collets for ¼" shaft and a suitable speed range











Dia.	Width	Shaft	Order No.	Optimal RPM	Max. RPM
1 ½"	1"	1/4"	07-X 110	8000	13,000
2″	1″	1/4"	07-X 120	6000	11,000

MOUNTING ACCESSORIES

Mandrels for use on straight grinders and drills

For use with	Shaft Dia.	Order No.
4" wheels	1/4"	07-X 004
	8mm	07-X 003
6" wheels	1/4"	07-X 006
	8mm	07-X 005





Extension mandrels for use on angle grinders

For use with	Thread	Order No.
4" and 6" wheels	M14	07-C 005
	5/8"-11	07-C 006



FX™ Cup Disc

- With 5/8"-11 threaded arbor for quick and easy mounting on angle grinders
- Trimmable for longest life and best performance
- No backing pad required









Dia.	Width	Arbor	Order No.	Optimal RPM	Max. RPM
4 ½"	3/4"	5/8"-11	07-X 450	6000	10,500

WALTER Surface Technologies

For a free demonstration in your plant call toll free: **1-888-592-5837**

Visit us on the web at: www.walter.com

Available at: