Surface Technolo	NFPA Hazard Rating							
MATERIAL S	AFETY DAT L124-E	Health 1 0 Reactivity						
	Sectio	n 1 - Product Ident		Light 2 = Moderate 3 =	= Serious 4 = Extreme			
J. WALTER INC.		rade name:	RPL PRO					
810 Day Hill Road	-	Product name:	RPL PRO					
Windsor, CT 06095		Order no.: VHMIS Classification:	53-D 252					
Emergency: INFOTRAC (800) 53		Controlled under WHMIS:	A, B5, D2B Yes					
	5 5055		103					
Section 2 - Hazardous Ingredients								
Ingredients	CAS Number	<u>% by Weight</u>	LD ₅₀ RA	T I	C ₅₀ RAT			
ALIPHATIC PETROL. DISTILLATE		60-100	>5000 mg/kg ORA		N/Av			
HYDROTREATED HEAVY	64742-52-5	10-30	N/Av		N/Av			
NAPHTHENIC DISTILLATE								
CARBON DIOXIDE	124-38-9	1-5	N/A		N/Av			
Physical state: Aerosol		ysical / Chemical	Characterist	iCS Odor threshold:	N/Av			
pH: N/A	Boiling point:			Freezing point:	N/AV N/Av			
Specific gravity: 0.80-0.85	Vapor pressu		20°C	Vapor density:	>1			
Evaporation rate: <1	VOC g/l:	1-5		Water solubility:	Negligible			
	Soction	4 - Fire & Explosi	on Hazard					
	Section		JITTIAZATU					
Flammability: Flammable Flashpoint: 77°C Tag closed-o Auto ignition temperature: N/Av Flammable limits (%): Upper: 8.8	on dioxide, dry che Hydrocarbon fume re combustion is in or static discharg	s and smoke. complete.						
	Sec	ction 5 - Reactivity	Data					
Chemical stability: Yes Reactivity conditions: N/A Incompatible substances: Stro Hazardous decomposition produ	ng oxidizing agents	Inder normal conditions umes and smoke. Carbon r	nonoxide where co	mbustion is incomp	olete			
N/A - Not Applicable					N/Av - Not Available Page 1 of 2			

Surface Techn	MATERIAL SAFETY DATA SHEET hnologies L-124E								
Section 6 - Toxicological Data									
-	effects Dizziness, e effects: Solv (TLV/TWA): See <u>Mutageni</u> N/Av	<u>city Re</u>	-	<u>Teratogenicity</u> N/Av	<u>Synergistic effects</u> N/Av				
Section 7 - Preventive Measures									
Protective equipr	respirator (NOISH/MSHATC 23C or equivalent) is recommended. Safety glasses.								
Waste disposal methods: Do not puncture or incinerate containers, even when empty. Dispose of in accordance wit state and federal regulations.				e of in accordance with local,					
Leak/spill procedures: Remove all sources of ignition. Use an inert absorbent material, and non-sparking tools. Prevent from entering a watercourse.				non-sparking tools. Ventilate area.					
Storage requirements:Keep away from heat, sparks, and open flames.Engineering controls:Ventilation - local (mechanical if used indoors on a continuous basis).									
Handling equipm			well ventilated area not to exceed 50°C						
Special shipping information: Consumer commodity (aerosol, UN1950, class 2.1)									
		Sectio	n 8 - First Aid M	easures					
Skin contact: Eye contact: Inhalation: Ingestion:	Wash thoroughly with soap and water. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. If affected by inhalation of vapor or spray mist, remove to fresh air. If swallowed, do not induce vomiting, get medical attention.				nd get medical attention.				
Other:	N/A								
Section 9 - Preparation of MSDS									
Prepared by: Telephone: Date:	Chemical Tools Manager 860-298-1100 May 1, 2008								
This data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.									

N/A - Not Applicable

N/Av - Not Available Page 2 of 2