			NFPA Hazard Rating
			Flammability
Surface Technologies			\wedge
Surface recimologies			$\sqrt{3}$
MATERIAL SAFETY		т	Health 1 0 Reactivity
_	_	- 1	\times \times
L-65E	· · ·		0 = Minimum 1 = Light 2 = Moderate 3 = Serious 4 = Extreme
	Section 1 - Proc	duct Ide	
J. WALTER INC.	Trade name:		Slap Shot PL
810 Day Hill Road	Product name:		Industrial parts cleaner/degreaser, safe on plastics
Windsor, CT 06095	Order no.:		53-C 553, 53-C 556, 53-C 557, 53-C 558
	WHMIS Classifica	ation:	B2, D2B
Emergency: INFOTRAC (800)-535-5053	Controlled under	WHMIS:	Yes
	Section 2 - Haza	rdous	ngredients
Ingredients CAS	S Number <u>% by</u>	Weight	LD50RAT LC50RAT
Distillate (petroleum) hydrotreated light 64	742-49-0 70	0 - 90	N/Av N/Av
Alcohol	67-63-0 10	0 - 30	5045 mg/kg 66100 mg/c.m. for 4 hours
Sectio	n 3 - Physical / C	Chemic	al Characteristics
Physical state: Liquid	Odor & appearance: L		
pH: N/Av	•.	> 60ºC	Freezing point: < - 30°C
Specific gravity: 0.72 g/ml @ 25°C		200 hPa	Vapor density: N/A
Evaporation rate: Fast	VOC g/I: 7	720	Water solubility: Non-miscible
	Section 4 - Fire &	، Explo	sion Hazard
Flammability: Yes Conditions: Av	oid flame, spark or any o	other energ	y source.
Flashpoint: - 24°C	Exting	uishing m	edia: Foam, dry powder, CO ₂ .
Auto ignition temperature: 510°C	Hazaro	dous com	bustion products: Carbon monoxide and dioxide
Flammable limits (%): Upper: 13 Lower: 0	1,8 Sensit	ivity to me	echanical impact or static discharge: N/Av
	Section 5 - R	leactivi	ty Data
Chemical stability: Yes Conditions: Under normal conditions. Incompatible substances: Oxidizing agents	3	onditions	: Keep away from ignition source.
Hazardous decomposition products: N/A	v		
N/A - Not Applicable			N/Av - Not Available
			Page 1 of 2
			-9

Acute exposure eff Chronic exposure	effects: Frequent and long skin contact can cause irritation and inflammation. effects: Prolonged contact may cause skin and eye irritation.				
Acute exposure eff Chronic exposure Exposure limits (TI Carcinogenicity	effects: Frequent and long skin contact can cause irritation and inflammation. effects: Prolonged contact may cause skin and eye irritation.				
	Route of entry: Eye and skin contact, inhalation, ingestion. Acute exposure effects: Frequent and long skin contact can cause irritation and inflammation. Chronic exposure effects: Prolonged contact may cause skin and eye irritation. Exposure limits (TLV/TWA): N/Av				
	MutagenicityReproductive toxicityTeratogenicitySynergistic effectsNoNoNoNo				
If yes to any of the	above, specify:				
	Section 7 - Preventive Measures				
Protective equipme Handling procedur Waste disposal me Leak/spill procedur Storage requireme Engineering contro Handling equipmer Special shipping ir	es:Follow instructions on packaging.thods:Dispose as per local, state and federal regulations.res:Soak up with absorbent material, place in approved container.nts:Store below 50°C.ols:Provide adequate ventilation.nt:N/Av				
	Section 8 - First Aid Measures				
Skin contact: Eye contact: Inhalation: Ingestion: Other:	Rinse with water until substance is removed from skin. Rinse eyes thoroughly with water for 20 minutes. Consult a physician if needed. Remove victim to fresh air. Do not give stimulants. Consult a physician if needed. Do not induce vomiting. Do not give stimulants. Consult a physician if needed. Consult a physician if necessary.				
	Section 9 - Preparation of MSDS				
Prepared by: Telephone: Date:	Chemical Tools Manager 860-298-1100 May 1, 2008				
recommended industri	good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The al hygiene and safe handling procedures are believed to bee generally applicable. However, each user should review these ne specific context of the intended use and determine whether they are appropriate.				
N/A - Not Applicab	le N/Av - Not Avai				