

AF-PL™

DESCRIPTION

AF-PL is specially formulated to effectively dissolve and remove grease, oil and other contaminants where plastics and rubber-like compounds are present.

- Quick acting
- Penetrates and displaces moisture
- Effectively cuts through and removes grease, oil, paint, ink, glue, adhesive, wax, dirt and grime
- Fast evaporation
- Residue-free
- Safe on plastics and rubber-like compounds
- Free of chlorinated solvents, CFC and HCFC
- Aerosol: strong jet blasts away contaminants

APPLICATIONS

Use AF- PL for:

- Cleaning of metal parts in presence of plastic or gaskets
- Maintenance, repair and overhaul of motors, machinery, vehicles and equipment
- Removal of glue, paint, ink, resin, sealant and flux residue
- Cleaning of electric components, instruments, lenses, glass, chains, gears, cables, etc...

RECOMMENDATIONS FOR USE

- Spray directly on parts

TECHNICAL DATA

Physical state: Citrus sent, colorless

Density: 0.72g/ml@25°C (77°F)

Flash point: -24°C (-11.2°F)

Engineering controls: Ensure adequate ventilation

Incompatible substances: Oxidizing agents

WHMIS: liquid B2, D2B

Shelf life: 2 years in closed container, stored in ideal conditions

Shipping: liquid U.N. 1993, Class 3, P.G.II

ORDERING INFORMATION

Description	Size	Order No.	MSDS
Trigger sprayer	500ml	53-C 553	L-65
Liquid	5 L	53-C 556	L-65
Liquid	20 L	53-C 557	L-65
Liquid	200 L	53-C 558	L-65

Accessories

Air Force PL refillable sprayer	53-M 101
Industrial pump sprayer	53-L 120
Repl. trigger spray bottle 500ml	53-L 312
Valve for 20L pail /	53-L 208 /
200L drum (3/4")	
Valve for 200L drum (2")	53-L 209