

# BIO-CIRCLE **ULTRA**™

## Super-Duty Bioremediating Parts Cleaner / Degreaser

BIO-CIRCLE **ULTRA**<sup>™</sup> is an innovative, pH neutral cleaner specifically designed for use with BIO-CIRCLE<sup>®</sup> parts cleaning systems. The highly effective *ULTRA* formula quickly removes toughest, hardened oil/grease as well as other tough to remove contaminants from parts while maintaining its cleaning power over time thanks to the self-cleaning action of natural bioremediation. Yet, it is the safest & most effective replacement for hazardous solvents in manual parts cleaning applications. It eliminates health & safety risks and frequent waste disposal.

### Features & Benefits:

- Ultra powerful & fast cleaning action
- Non-stick formula helps lift and flush away toughest grease & grime
- Self-cleaning action maintains cleaning efficiency over time
- Non-toxic, non-flammable, VOC-free, pH neutral
- Safe on all metals and most surfaces
- Contains temporary corrosion inhibitors
- Free of CFC and HCFC
- NSF Category C1, Register #145549

### **Applications:**

BIO-CIRCLE **ULTRA**<sup>™</sup> removes:

- Toughest mineral & natural oils, grime
- Adhesive lubricants
- Corrosion protection coatings
- Carbon deposits
- All cutting lubricants
- Most NLGI 2 and lower, mineral greases, more specifically:
  - Chassis and bearing grease
  - Polyuera grease
  - Impact grease
  - Water resistant bearing grease
  - High temperature moly grease
- Food grade grease
- Fresh tar and resin products



# BIO-CIRCLE L<sup>TM</sup> ULTRA

### **Recommendations for Use:**

- Wear nitrile gloves
- Do not dilute
- Use only with the BIO-CIRCLE<sup>®</sup> parts cleaning systems
- Do not soak components with rubber parts

#### **Technical Information**

Working temp.	Up to 43°C (109°F)		
Microorganisms	Naturally occurring, BSL/CL 1 (non-pathogen)		
Density	1.005 g/ml ( at 68°F)		
Flashpoint	None		
Color/Odour	Cloudy, Soapy		
рН	8.5 to 9		
Rinsability	Complete with water		
Incompatible	solvent, biocides, alkaline, acid and chlorinated solutions		
substances			
VOC	0% w/w		
Storage	5°C to 25°C (40°F to 77°F), 1 year max. for best results		

Description	Size		Order No.	(M)SDS
	Metric	Imperial		
Liquid	20L	5.2 gal.	55-A 107	L-148E
Liquid	208L	55 gal.	55-A 108	L-148E
Liquid	1000L	264 gal.	55-A 109	L-148E

#### ACCESSORIES

Spout for 20L pail	53-L 207
Faucet for 208L drum, 2"	53-L 209
Faucet for 208L drum, ¾"	53-L 210
Transfer hand pump	55-B 051

(M)SDS available upon request or visit our web site at www.walter.com Not for product specification. The technical data contained herein is intended as reference only and may change without notice.