

BOLT-OUT™

DESCRIPTION

Bolt –out is a premium penetrating lubricant which is a heavy-duty, non chlorinated formula that initially penetrates and then lubricates seized parts while inhibiting further rust in a wide range of temperatures. Its Microscopic ‘Moly’ particles provide excellent lubrication and protection. Bolt-out has the following benefits:

- It displaces moisture
- It is silicone free
- Approved for use in food plants
- Contains no CFC, HCFC or chlorinated solvents.
- Faster disassembly with less effort
- Non flammable liquid

APPLICATIONS

Bolt-Out can be used in industries as well as workshops. It is effective in a wide range of temperature (-20°C to 250°C). It is created for:

- Disassembly of seized bolts, nuts, mechanisms, pins bushing, etc.
- Loosening of hoists, pulley blocks, hinges.
- Eliminating squeaking noise from moving parts.
- Maintenance, repair, overhaul, re-building.
- Plant shut-downs and fleet maintenance

DIRECTIONS FOR USE

Shake can very well before use. Remove loose rust and excess dirt. Spray on seized parts and allow time for penetration before disassembling.

TECHNICAL DATA

Physical state: Aerosol

PH: N/Av

Specific gravity: 0,79 g/ml @ 20°C

Flammability: Yes

Conditions: Source of ignition.

Flashpoint: -60°C for propellant

Working temperature: Effective from -20°C to 250°C (-5°F to 482°F)

Engineering controls: Ensure adequate ventilation.

Incompatible substances: Strong oxidizing agents.

Storage: Store below 50°C.

Shelf life: 2 years in closed container, stored in ideal conditions

Shipping: Aerosol, U.N. 1950, CLASS 2,1.

WHMIS: A, B1, D2B

ORDERING INFORMATION

Description	Size	Order No.	MSDS
Aerosol	400ml (332g)	53-D 892	L-08E
Sprayer	500ml	53-D 893	L-26E
Liquid	20L	53-D 897	L-26E

MSDS available upon request or on our web site at www.walter.com