

CHAIN GANG™

DESCRIPTION

Chain Gang™ is a high performance, synthetic lubricant, which is designed to penetrate fine clearance and seals out dust, dirt and water. It contains `Moly` for high load lubrication and prevents metal-to-metal contact. The unique formula will penetrate, lubricate and protect moving parts by reducing friction and wear that causes metal fatigue. Regular use of Chain Gang™ will help inhibit corrosion, reduce load stress and greatly extend chain life. This product does not attract dirt particles, it is suitable for wet conditions and it provides effective corrosion protection.

APPLICATIONS

Chain Gang™ is recommended for use as a lubricant and corrosion inhibitor on:

- All types of chain drives and wire rope
- O-ring chains
- Machinery
- Forklifts
- Also effective on wire cables
- Eliminating metal to metal contact
- High load lubrication
- Use under wet conditions

DIRECTIONS FOR USE

Shake very well before use.
From a distance of 25cm (10 in.) spray a small amount directly onto parts.

Clean up :

Use Walter Slap Shot™ 53-C 502

TECHNICAL DATA

Physical state: Aerosol

Density: 0.71 g/ml (20°C/68°F)

VOC: 54.3% (w/w)

Flash Point: Not available

Working temperature: -20°C to 150°C
(-4°F to 302°F)

Engineering controls: Provide adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Store below 50°C/122°F.

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	MSDS
Aerosol	400ml	53-D102	L-05E

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice