

FOOD ZONE V

Heavy Duty food grade lubricant

Industrial lubricant for heavy duty applications and chains lubrication in food and beverages processing environments

Features & benefits

- NSF approved H1 FOOD GRADE LUBRICANT for incidental contact with food
- Thick non drying film to extend equipment life and lubricate moving and sliding parts
- Foaming formula for maximum penetration and adherence
- PTFE additives for maximum wear and friction protection
- Plastic and rubber compatible
- Non-conductive
- Water resistant
- Resists chemical attack
- Temperature range: -35°C /-31°F to 135°C/275°F
- Temporary corrosion protection

DESCRIPTION	SIZE	ORDER NO.	MSDS
Aerosol	400 ml / 13.5 oz	53 D 652	L-154

Remove with:

Slap Shot aerosol, 500ml 53-C 502
 Slap Shot sprayer, 500ml 53-C 503
 Slap Shot, 5L 53-C 506
 Slap Shot, 20L 53-C 507
 Slap Shot, 200L 53-C 508
 Slap Shot PL aerosol, 500ml 53-C 552

Technical information

Density@20°C (68°F)	0.79g/cm ³
VOC	14.5%
Odor/color	Mild/whitish
Dielectric Strength	Non conductive
Solubility in water	Not miscible or difficult to mix
Viscosity	N/D

MSDS available upon request or visit our web site at www.walter.com