

FOOD ZONE

Food grade general purpose lubricant

Multi-purpose lubricant and penetrating oil for food industry plants.

Features & benefits

- NSF approved H1 FOOD GRADE LUBRICANT for incidental contact with food
- Excellent and fast penetration of rust, scale and general dirt and grime, to loosen seized and rusted parts
- Displaces water and moisture
- Leaves a thin protective film
- Non-conductive
- Water resistant
- Resists chemical attack
- Temperature range: -10°C /14°F to 180°C/356°F
- CO2 non flammable propellant

DESCRIPTION	SIZE	ORDER NO.	MSDS
Aerosol	400 ml / 13.5 oz	53 D 602	L-153

Remove with:

Slap Shot aerosol, 500ml 53-C 502
 Slap Shot sprayer, 500ml 53-C 503
 Slap Shot, 5L 53-C 506
 Slap Shot, 20L 53-C 507
 Slap Shot, 200L 53-C 508
 Slap Shot PL aerosol, 500ml 53-C 552

Technical information

Density@20°C (68°F)	1.19g/cm ³
Flash Point	62°C /144°F
Odor/color	Mild/yellow
Dielectric Strength	Non conductive
Solubility in water	Not miscible or difficult to mix
Viscosity	N/D

MSDS available upon request or visit our web site at www.walter.com