

FOOD ZONE™

Food Grade General Purpose Lubricant

Multi-purpose lubricant and penetrating oil for food industry plants.

Features & benefits

- NSF approved H1 FOOD GRADE LUBRICANT for incidental contact with food (registration number 148372)
- Excellent and fast penetration of rust, scale and general dirt and grime, to loosen seized and rusted parts
- Displaces water and moisture
- Leaves a thin protective film
- Non-conductive
- Water resistant
- Resists chemical attack
- Temperature range: -10°C to 180°C (14°F to 356°F)
- CO₂ nonflammable propellant

DESCRIPTION	SIZE	ORDER NO.	(M)SDS
Aerosol	400 ml / 13.5 oz	53 D 602	L-153E

Remove with:

Slap Shot aerosol, 500ml 53-C 502
 Slap Shot sprayer, 500ml 53-C 503
 Slap Shot, 5L 53-C 506
 Slap Shot, 20L 53-C 507
 Slap Shot, 200L 53-C 508
 Slap Shot PL aerosol, 500ml 53-C 552

Technical information

Density (20°C/68°F)	1.19g/ml
VOC	39.2% (w/w)
Flash Point	62°C /144°F
Odor/color	Mild/yellow
Dielectric Strength	Non conductive
Solubility in water	Not miscible or difficult to mix
Viscosity	N/D
Shelf Life	2 years in closed container

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice