

# OMNI™

## Cleaner/Lubricant/Protector

OMNI™ is a multi-functional maintenance cleaner, lubricant and protector. OMNI™ is capable of removing stubborn grease and oils, dissolves flash rust and graphite, exhibits excellent penetrating and lubricating capability and protects surfaces from oxidation. OMNI™ is truly the all-in-one product!

### Features & Benefits:

- Powerful multi-functional maintenance cleaner/lubricant/protector made from highly refined oils
- Excellent creeping capacity
- Loosen rusted and seized hardware
- Eliminates squeaks from moving parts
- Reduces friction and wear
- Displaces moisture and provides temporary corrosion protection
- Cleans greases and oils
- Dielectric strength 350 Volts/Mil, dielectric breakdown voltage 35 000 Volts as per ASTM D877-13, procedure A
- Non-flammable
- Free of CFC and HCFC
- VOC compliant (per CARB 310)
- NSF registered (category code A8, registration number 142610)
- Accepted for food plants in Canada

Description	Size		Order No.	(M)SDS
	Metric	Imperial		
Aerosol	480ml	16.2 fl. oz	53-X 002	L-73E
Trigger sprayer	500ml	16.9 fl. oz.	53-X 003	L-74E
Liquid	3.78L	1 gal.	53-X 005	L-74E
Liquid	20L	5.2 gal.	53-X 007	L-74E
Liquid	208L	55 gal.	53-X 008	L-74E
Liquid	1000L	264 gal.	53-X 009	L-74E

### ACCESSORIES

Industrial pump sprayer	53-L 120
Spout for 5L pail	53-L 113
Spout for 20L pail	53-L 207
Faucet for 208L drum, 2"	53-L 209
Faucet for 208L drum, ¾"	53-L 210
Replacement trigger sprayer	53-L 314

### Technical Information

<b>Density</b>	0.81 g/ml (at 68°F)
<b>Flashpoint</b>	125°C (257°F)
<b>Odor/color</b>	Vanilla/ Clear
<b>pH</b> (at 100g/L H <sub>2</sub> O)	N/A
<b>Rinsability</b>	Insoluble
<b>VOC</b>	4.69% (CARB 310)

(M)SDS available upon request or visit our web site at [www.walter.com](http://www.walter.com)

Not for product specification. The technical data contained herein is intended as reference only and may change without notice