

SLAP SHOT™

DESCRIPTION

A rapid-evaporating, fast acting cleaner/degreaser, that completely dissolves and washes off stubborn dirt and grease without leaving a residue. Displaces moisture and prepares surfaces for subsequent treatment such as painting or re-lubrication. For use when an ultra clean surface is required and as a high performance alternative to 1,1,1-trichloroethylene.

- Get the job done in one operation.
- Prepares surfaces for painting or re-lubrication.
- Chlorinated solvent free.
- No rinsing, no residue.
- Fast evaporation.
- Safe on all metals.
- Aerosol jet with strong jet to blast away tough grime.
- Dissolves grease and oil quickly and completely.
- Displaces moisture.

APPLICATIONS

Contaminants:

Removes oil, grease, paint, ink, glue, adhesive, wax and rubber.

Surfaces:

All metals. For example machine parts, engines, gears, cables, chains, forklifts, cranes, pumps and industrial equipment.

Directions for Use:

Shake well before use. Spray or apply onto soiled surfaces.

TECHNICAL DATA

Physical state: Aerosol or liquid

Appearance: Clear liquid, kerosene odour

Density: 0.72 g/ml (20°C/ 68°F)

VOC: 74.4%(w/w) to 77.7% (w/w)

Flashpoint: -60°C/ -76°F (Aerosol)
-24°C/ -11.2°F (Liquid)

Solubility in water : Not miscible

Engineering controls: Provide adequate ventilation

Incompatible substances: Oxidizing agents

Storage: Keep container tightly closed, store below 50°C/122°F.

Shelf life: 2 years in closed container, stored in ideal conditions

ORDERING INFORMATION

Description	Size	Order No.	(M)SDS
Aerosol	500 ml	53-C 502	L-39E
Sprayer	500ml	53-C 503	L-40E
Liquid	5 L	53-C 506	L-40E
Liquid	20 L	53-C 507	L-40E
Liquid	200 L	53-C 508	L-40E

Accessories

Refillable trigger sprayer bottles 53-L 311

Spout 20L/ 200L drum (3/4") 53-L 208

(M)SDS available upon request or visit our web site at www.walter.com

Not for product specification. The technical data contained herein is intended as reference only and may change without notice