

# **CONTACT CLEAN™**

## DESCRIPTION

Contact Clean<sup>™</sup> is a non-flammable cleaner for removing grease, oil, and contaminants from sensitive electronics and electrical equipment to prevent contact failure.

- Nonflammable and nonconductive
- Effectively cuts through and removes grease, oil, and dirt
- Fast-evaporating formula dries residue-free in seconds
- Strong aerosol jet
- NSF category K2, registration #154540.
- VOC compliant (per Carb 310)

### APPLICATIONS

- Removing contaminants from electrical parts
- Safely cleans most plastics and rubber compounds
- Instrument and equipment junction cleaning (PLCS, printed circuit boards, vehicle fuse boxes).

*Directions for Use:* Shake well before use. Spray on soiled surfaces.

### **TECHNICAL DATA**

Physical state: Aerosol Appearance: Clear liquid, ether-like odour Density: 1.41g/ml (20°C /68°F) VOC: 23.20 % (w/w) (CARB 310) Kauri-Butanol Value (KB), ASTM D 1133-61: 20.0 Surface Tension, ASTM D 1331: 15.99 mN/m (dynes /cm) Flash Point: This material is classified as non-flammable per UNECE classification procedures Engineering controls: Provide adequate ventilation Incompatible substances: Oxidizing agents Storage: Keep container tightly closed, store below 50°C/122°F Shelf life: Two (2) years in closed container, stored in ideal conditions

### **ORDERING INFORMATION**

Description	Size	Order No.	(M)SDS
Aerosol	340g	53-C 712	L-165

(M) SDS available upon request or visit our web site at <u>www.walter.com</u> Not for product specification. The technical data contained herein is intended as reference only and may change without notice.