

SAFETY DATA SHEET

PURE SHOT

| Section 1. Identification | | |
|--|--|--|
| Product identifier | : PURE SHOT | |
| Product code | : 53-C 702 | |
| Other means of identification | : L-80E | |
| Product type | : Aerosol. | |
| Relevant identified uses o | of the substance or mixture and uses advised against | |
| Identified uses | : Cleaner. | |
| Manufacturer | : Walter Surface Technologies Inc. 5977 Trans Canada Highway Pointe-Claire, QC H9R 1C1 Canada info@walter.com www.walter.com General Information: 1-888-592-5837 | |
| Emergency telephone number (with hours of operation) | : INFOTRAC [®] 1-800-535-5053. International call collect: 1-352-323-3500 24 hours/day, 7 days/week. | |

Section 2. Hazard identification

| Classification of the substance or mixture | FLAMMABLE AEROSOLS - Category 1 GASES UNDER PRESSURE - Compressed gas SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION (Fertility) - Category 1 TOXIC TO REPRODUCTION (Unborn child) - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3 |
|--|---|
| <u>GHS label elements</u> Hazard pictograms | |

: Danger



Signal word



Section 2. Hazard identification

| Hazard statements | H222 - Extremely flammable aerosol. H280 - Contains gas under pressure; may explode if heated. H319 - Causes serious eye irritation. H315 - Causes skin irritation. H360 - May damage fertility or the unborn child. H351 - Suspected of causing cancer. H335 - May cause respiratory irritation. H336 - May cause drowsiness or dizziness. H373 - May cause damage to organs through prolonged or repeated exposure. H412 - Harmful to aquatic life with long lasting effects. |
|---|--|
| Precautionary statements | |
| Prevention | P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P280 - Wear protective gloves. Wear protective clothing. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P260 - Do not breathe dust or mist. P264 - Wash hands thoroughly after handling. P251 - Do not pierce or burn, even after use. |
| Response | P314 - Get medical attention if you feel unwell. P308 + P313 - IF exposed or concerned: Get medical attention. P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P302 + P352 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. P332 + P313 - If skin irritation occurs: Get medical attention. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention. |
| Storage | P405 - Store locked up. P410 - Protect from sunlight. P412 - Do not expose to temperatures exceeding 50°C/122°F. P403 - Store in a well-ventilated place. |
| Disposal | P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations. |
| Other hazards which do not result in classification | : None known. |

Section 3. Composition/information on ingredients

| Substance/mixture | : | Mixture |
|-------------------|---|---------|
| Other means of | : | L-80E |
| identification | | |

| Ingredient name | % (v/v) | CAS number |
|-----------------|----------|------------|
| 1-Bromopropane | 80 - 100 | 106-94-5 |

The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.



Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-aid measures

| Description of necess | sary first aid measures |
|------------------------------|---|
| Eye contact | : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention. |
| Inhalation | : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Skin contact | : Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse. |
| Ingestion | : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. |

Most important symptoms/effects, acute and delayed

| Potential acute health effects | |
|--------------------------------|---|
| Eye contact | : Causes serious eye irritation. |
| Inhalation | : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation. |
| Skin contact | : Causes skin irritation. |
| Ingestion | : Can cause central nervous system (CNS) depression. |
| Over-exposure signs/sympto | <u>ms</u> |
| Eye contact | : Adverse symptoms may include the following: pain or irritation watering redness |





PURE SHOT

Section 4. First-aid measures

| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weight increase in fetal deaths skeletal malformations |
|----------------------------|---|
| Skin contact | : Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations |
| Ingestion | : Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations |
| Indication of immediate me | dical attention and special treatment needed, if necessary |
| Notes to physician | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| Specific treatments | : No specific treatment. |
| Protection of first-aiders | : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. |

See toxicological information (Section 11)

Section 5. Fire-fighting measures

| Extinguishing media | |
|--|--|
| Suitable extinguishing media | : Carbon dioxide, dry chemical, foam and water fog or spray. |
| Unsuitable extinguishing media | : Do not use water jet. |
| Specific hazards arising from the chemical | : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |



Section 5. Fire-fighting measures

| Hazardous thermal decomposition products | Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds carbonyl halides |
|--|--|
| Special protective actions for fire-fighters | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. |
| Special protective equipment for fire-fighters | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
|--------------------------------|----|--|
| For emergency responders | : | If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. |
| Methods and materials for co | nt | ainment and cleaning up |

Spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.





PURE SHOT

Section 7. Handling and storage

Precautions for safe handling

| Protective measures | Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. |
|--|--|
| Advice on general occupational hygiene | Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas. |
| Conditions for safe storage, including any incompatibilities | Store in accordance with local regulations. Do not expose to temperatures exceeding 50°C/122°F. This product should be stored away from sources of strong heat, oxidizing agents, reducing agents, and strong acids. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use. |

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|-----------------|---|
| 1-Bromopropane | CA British Columbia Provincial (Canada, 7/2016). TWA: 10 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 10 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 ppm 15 minutes. TWA: 10 ppm 8 hours. |

| Appropriate engineering controls | : | No personal respiratory protective equipment normally required. Avoid breathing dust/fume/gas/mist/vapors/spray. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. |
|-------------------------------------|-----|--|
| Environmental exposure controls | : | Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. |
| Individual protection measu | res | |
| Hygiene measures | : | Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and |

safety showers are close to the workstation location.



Surface Technologies

Section 8. Exposure controls/personal protection

| • | · · · |
|------------------------|---|
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. |
| Other skin protection | Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. |

Section 9. Physical and chemical properties

| _ | |
|--|--|
| <u>Appearance</u> | |
| Physical state | : Gas. |
| Color | : Clear. |
| Odor | : Sweet. |
| Odor threshold | : Not available. |
| рН | : Not available. |
| Melting point | : -129.5°C (-201.1°F) (1-Bromopropane) |
| Boiling point | : 63.4°C (146.1°F) (1-Bromopropane) |
| Flash point | : Closed cup: -25.5°C (-13.9°F) (1-Bromopropane) |
| Evaporation rate | : Not available. |
| Flammability (solid, gas) | : Flammable liquid. |
| Lower and upper explosive (flammable) limits | : Lower: 4.6% (1-Bromopropane) Upper: 7.8% (1-Bromopropane) |
| Vapor pressure | : 227 kPa (1702.64 mm Hg) [room temperature] (1-Bromopropane) |
| Vapor density | : Not available. |
| Relative density | : 4.34 (1-Bromopropane) |
| Solubility | : Not available. |
| Solubility in water | : 2.5 g/l (1-Bromopropane) |
| Partition coefficient: n- octanol/water | : Not available. |
| Auto-ignition temperature | : 370°C (698°F) (1-Bromopropane) |

Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

Section 9. Physical and chemical properties

| Decomposition temperature | 1 | Not available. |
|---------------------------|---|----------------|
| Viscosity | 1 | Not available. |
| Flow time (ISO 2431) | 1 | Not available. |
| VOC content | 1 | 85 % (w/w) |
| Aerosol product | | |
| Type of aerosol | 1 | Spray |

Section 10. Stability and reactivity

| Reactivity | : No specific test data related to reactivity available for this product or its ingredients. |
|------------------------------------|--|
| Chemical stability | : The product is stable. |
| Possibility of hazardous reactions | : Under normal conditions of storage and use, hazardous reactions will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). |
| Incompatible materials | : Reactive or incompatible with the following materials: oxidizing materials, reducing materials and acids. Do not mix with finely divided alkali or alkaline earth metals. May attack some plastics, rubbers, and coatings. |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------|---------|------------|----------|
| 1-Bromopropane | LD50 Oral | Rat | 3600 mg/kg | - |

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|--|
| 1-Bromopropane | - | 2B | Reasonably anticipated to be a human carcinogen. |

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Section 11. Toxicological information

| Name | | Category | Target organs |
|--|---|---|---|
| 1-Bromopropane | | Category 3 | Respiratory tract irritation and Narcotic effects |
| Specific target organ toxic | city (repeated exposure | <u>e)</u> | |
| Name | | Category | Target organs |
| 1-Bromopropane | | Category 2 | Not determined |
| Aspiration hazard There is no data available. | | | |
| nformation on the likely routes of exposure | : Dermal contact. E | ye contact. Inhalation. I | ngestion. |
| Potential acute health effec | <u>ts</u> | | |
| Eye contact | : Causes serious ey | e irritation. | |
| Inhalation | | l nervous system (CNS) ause respiratory irritation |) depression. May cause drowsiness or n. |
| Skin contact | : Causes skin irritat | ion. | |
| Ingestion | : Can cause central | nervous system (CNS) |) depression. |
| Symptoms related to the pl | nysical, chemical and t | oxicological characte | <u>ristics</u> |
| Eye contact | : Adverse symptom pain or irritation watering redness | s may include the follov | ving: |
| Inhalation | : Adverse symptom respiratory tract in coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness reduced fetal weig increase in fetal de skeletal malformat | g e Iht eaths | ving: |
| Skin contact | : Adverse symptom irritation redness reduced fetal weig increase in fetal de skeletal malformat | eaths | ving: |
| Ingestion | : Adverse symptom reduced fetal weig increase in fetal de skeletal malformat | eaths | ving: |

<u>Delayed and immediate effects and also chronic effects from short and long term exposure</u> <u>Short term exposure</u>

Section 11. Toxicological information

| | | - |
|--------------------------------|----|--|
| Potential immediate effects | : | No known significant effects or critical hazards. |
| Potential delayed effects | 1 | No known significant effects or critical hazards. |
| <u>Long term exposure</u> | | |
| Potential immediate effects | : | No known significant effects or critical hazards. |
| Potential delayed effects | 1 | No known significant effects or critical hazards. |
| Potential chronic health effe | ct | <u>S</u> |
| General | 1 | May cause damage to organs through prolonged or repeated exposure. |
| Carcinogenicity | : | Suspected of causing cancer. Risk of cancer depends on duration and level of exposure. |
| Mutagenicity | 1 | No known significant effects or critical hazards. |
| Teratogenicity | 1 | May damage the unborn child. |
| Developmental effects | 1 | No known significant effects or critical hazards. |
| Fertility effects | : | May damage fertility. |
| | | |

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|------------|
| Oral | 4800 mg/kg |

Section 12. Ecological information

| <u>Toxicity</u> | | | | |
|-------------------------|-----------------------------------|----------------------------|----------|--|
| Product/ingredient name | Result | Species | Exposure | |
| 1-Bromopropane | Acute LC50 67300 µg/L Fresh water | Fish - Pimephales promelas | 96 hours | |

Persistence and degradability

There is no data available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| 1-Bromopropane | 2.1 | - | low |

Mobility in soil

| Soil/water | partition |
|-------------|-----------|
| coefficient | (Koc) |

: Not available.

Other adverse effects

: No known significant effects or critical hazards.





Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

| | TDG Classification | IMDG | ΙΑΤΑ |
|-------------------------------|---|--|---|
| UN number | UN1950 | UN1950 | UN1950 |
| UN proper shipping name | Aerosols, flammable (each not exceeding 1 L capacity) | Aerosols, flammable (each not exceeding 1 L capacity) | Aerosols, flammable (each not exceeding 1 L capacity) |
| Transport hazard class(es) | 2.1 | 2.1 | 2.1 |
| Packing group | - | - | - |
| Environmental hazards | No. | No. | No. |

Additional information

TDG Classification

: Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).

Emergency Response Guidebook (ERG)

: 126

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

| <u>Canadian lists</u> | |
|--------------------------------|---|
| Canada inventory (DSL NDSL) | : All components are listed or exempted. |
| Canadian NPRI | : The following components are listed: Norflurane |
| CEPA Toxic substances | : The following components are listed: Norflurane |





Section 16. Other information

Procedure used to derive the classification

| Classification | Justification |
|--|-----------------------|
| FLAMMABLE AEROSOLS - Category 1 | On basis of test data |
| GASES UNDER PRESSURE - Compressed gas | On basis of test data |
| SKIN CORROSION/IRRITATION - Category 2 | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A | Calculation method |
| CARCINOGENICITY - Category 2 | Calculation method |
| TOXIC TO REPRODUCTION (Fertility) - Category 1 | Calculation method |
| TOXIC TO REPRODUCTION (Unborn child) - Category 1 | Calculation method |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) | Calculation method |
| (Respiratory tract irritation) - Category 3 | |
| SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic | Calculation method |
| effects) - Category 3 | |
| SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - | Calculation method |
| Category 2 | |
| AQUATIC HAZARD (ACUTE) - Category 3 | Calculation method |
| AQUATIC HAZARD (LONG-TERM) - Category 3 | Calculation method |

History

| Date of issue Date of previous issue Version | : 08/30/2018 : Not applicable : 1 |
|--|--|
| Prepared by | : KMK Regulatory Services Inc. |
| Key to abbreviations | ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations HPR = Hazardous Products Regulations |

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

